



Color Variants

VI230134

Aluminium control panel

Width 28 cm

VI230114

Stainless steel control panel

Width 28 cm

Optional accessories

VD201034

Shot-blasted aluminium appliance cover

Installation Accessories

SH230001

Hinge holder for fitting the appliance cover

VV200034

Aluminium connection strip for combination with further Vario cooktops

Product Variants

VI230114

Vario induction cooktop 200 series

Stainless steel control panel

Width 28 cm

VI230134

Vario induction cooktop 200 series

Aluminium control panel

Width 28 cm

Can be combined with the cooktops of the Vario 200 series to a harmonic unity.

Generous control panel for comfortable and secure operation.

Cooking zones

1 induction cooking zone ø 21 cm (2200 W, with booster 3300 W).

1 induction cooking zone ø 15 cm (1400 W, with booster 1800 W).

Handling

Control knobs with cooking zone and output level markings.

Electronic power control in 9 output levels.

Features

Cooking zone marking.

Pot detection.

Booster function for both cooking zones.

Safety

Residual heat indication.

Operation indicator.

Safety shut-off.

Planning notes

Operates with magnetic (induction) iron pots and pans only. For an optimal heat distribution, the use of sandwich bottom cookware is recommended. Immersion depth 50 mm.

The wok pan WP 400 001 cannot be used with this appliance.

Appliance must be fixed from underneath.

Cooktop clamping range: 20 - 40 mm.

Connection

Total connected load 3.7 kW.

Connecting cable 1.5 m without plug.

Characteristics

Product name/family

Vario/Domino cooking zone cera

Built-in / Free-standing

CONSTR_TYPE.Built-in

Energy input

Electric

Total number of positions that can be used at the same time

2

Required niche size for installation (HxWxD)

50 x 268 x 490

Width of the product (mm)

288

Dimensions of the product (mm)

50 x 288 x 523

Net weight (kg)

7.0

Gross weight (kg)

8.0

Residual heat indicator

Separate

Location of control panel

Hob front

Basic surface material

Ceramic

Color of surface

Alu, Black

Color of frame

Alu

Approval certificates

AENOR, CE

Length of electrical supply cord (cm)

150

EAN code

4242006194307

Consumption and connection features

Electrical connection rating (W)

3700

Gas connection rating (W)

Current (A)

16

Voltage (V)

220-240

Frequency (Hz)

60; 50

created on 2017-01-19

Page 1

